EP-RGB-20-RC RF REMOTE

Product Introduction

Control flexible and rigid LED Lights. Suitable for 5050, 3528 or 335 LED strips and bars. RGB or 3 x Single colors with EP-RGB-20-RC controller.

RF CONTROLLER

Rf Ra

 (\pm)

Specification

()

-20-60 C
DC 12-24V is default, 5V is optional
3 channels
433MHz
10~15M
L128 xW64 xH24 mm
L85xW52xH7 MM
L145 x W95 x H50mm
165g
205g
<1 W
<4A (each channel)
<60W, 12V: <144W, 24V: <288W

Remarks

Remote Control: 20key RF

Key Function

1	On/Off	On/off lights
2	Play/Stop	
3	Brightness UP	
4	Brightness DOWN	
5	Red	
6	Green	
7	Blue	
8	White	
9	Orange	
10	Yellow	
11	Cyan	
12	Pink	
13	Auto	All modes in circle
14	3 Colour step change	Speed and brightness are adjustable

15	3 Colour fade change	Speed is adjustable, brightness is not
16	Speed Increase	he program speed will add up once pressed
17	Seven Colours flash frequency	Speed and brightness are adjustable
18	3 Colour step change	
19	3 Colour fade change	Speed is adjustable, brightness is not
20	Speed Decrease	The program speed will slow down once pressed



Wiring Diagram

(-)

