



PROFIL			
	length	surface finishing	item number
	1m (standard) 2m (standard) 2 - 6m (special order)	non anodized (raw - aluminum)	IL-XTRU-3579

COVER	HR - LINE	length	cover	item number
		1m 2m	mleczna matt frosted	1316

END CAPS			item number
		end cap PCV	1384
		end cap PCV with hole	1445

BASE FOAM	HR - LINE	length	width	height	item number
		1240 mm	30 mm	10 - 100 mm	1466

(EN) FOAM BASE Functions:
 - selection of the right height of the foam base enables to level the HR-LINE Profile with the surface (such as different types of pavers)
 - „foam base“ is elastic – it cushions the loads to which the HR-LINE Profile is exposed
 - „foam base“ is a template for mouniting the HR-LINE Profile, during the pavers installation.

Applications :

- for flexible or hard LED strips up to 11.5 mm wide
- lighting or illumination of certain areas (stream of light may vary depending on the power of applied LEDs)
- different types of pavements, sidewalk surfaces, communication routes, bike lanes, driveways, parking lots
- profile construction makes it durable and sturdy, resistant to standard loads

Product Description :

Mounting :	plastic baseboard; ceramic glue (elastic, frost resistant) or cement
Ending element :	recommended Silicone – DOW CORNING 794 (transparent)
Certificate / Patent :	CE, patent rights

Advantages :

Fixture produces uniform line of light (not dotted) , designed to meet IP 67 waterproof level, environment friendly

* We reserve the right to change and modify our products.





